

FRAME OF LOVE - S design Moro, Pigatti.





Cornice

Anno di produzione: 2015 Versioni: standard, laccata. Materiali: Polietilene.

Dimensioni: 99 x 13 h 99 cm

Peso: 10 Kg

Imballaggio: 92 x 21 x 77 cm Volume imballaggio: 0,148 m³

Note: kit di appendimento incluso.

Cadre

Année de production: 2015 Versions: standard, laquée. Matériaux: Polyéthilène. Dimensions: 99 x 13 h 99 cm

Poids: 10 Kg

Emballage: 92 x 21 x 77 cm Volume emballage: 0,148 m³

Note: kit de suspension inclus.


Frame

Year of production: 2015 Versions: matt, lacquered. Material: Polyethylene. Dimensions: 99 x 13 h 99 cm

Weight: 10 Kg

Packaging: 92 x 21 x 77 cm Packaging volume: 0,148 m³

Note: hanging kit inluded.







FRAME OF LOVE - M design Moro, Pigatti.



Cornice

Anno di produzione: 2015 Versioni: standard, laccata. Materiali: Polietilene.

Dimensioni: 162 x 13 h 99 cm

Peso: 15 Kg

Imballaggio due scatole: 155 x 22 x 24 cm 31 x 31 x 100 cm

Volume imballaggio: 0,178 m³

Note: kit di appendimento incluso.

Cadre

Année de production: 2015 Versions: standard, laquée. Matériaux: Polyéthilène.

Dimensions: 162 x 13 h 99 cm

Poids: 15 Kg

Emballage deux boîtes: 155 x 22 x 24 cm 31 x 31 x 100 cm

Volume emballage: 0,178 m³

Note: kit de suspension inclus.

Frame


Year of production: 2015 Versions: matt, lacquered. Material: Polyethylene.

Dimensions: 162 x 13 h 99 cm

Weight: 15 Kg Packaging two boxes: 155 x 22 x 24 cm 31 x 31 x 100 cm

Packaging volume: 0,178 m³

Note: hanging kit inluded.







FRAME OF LOVE - L design Moro, Pigatti.





Cornice

Anno di produzione: 2009 Versioni: standard, laccata. Materiali: Polietilene.

Dimensioni: 162 x 13 h 162 cm

Peso: 18 Kg

Imballaggio due scatole: 155 x 22 x 24 cm 155 x 22 x 24 cm

Volume imballaggio: 0,164 m³

Note: kit di appendimento incluso.

Cadre

Année de production: 2009 Versions: standard, laquée. Matériaux: Polyéthilène.

Dimensions: 162 x 13 h 162 cm

Poids: 18 Kg

Emballage deux boîtes: 155 x 22 x 24 cm 155 x 22 x 24 cm

Volume emballage: 0,164 m³

Note: kit de suspension inclus.

Frame


Year of production: 2009 Versions: matt, lacquered. Material: Polyethylene.

Dimensions: 162 x 13 h 162 cm

Weight: 18 Kg Packaging two boxes: 155 x 22 x 24 cm 155 x 22 x 24 cm

Packaging volume: 0,164 m³

Note: hanging kit inluded.







FRAME OF LOVE - XL design Moro, Pigatti.





Cornice

Anno di produzione: 2015 Versioni: standard, laccata. Materiali: Polietilene.

Dimensioni: 223 x 13 h 162 cm

Peso: 23 Kg

Imballaggio tre scatole: 92 x 21 x 77 cm 155 x 22 x 24 cm 51 x 51 x 28 cm

Volume imballaggio: 0,302 m³ Note: kit di appendimento incluso. Cadre

Année de production: 2015 Versions: standard, laquée. Matériaux: Polyéthilène.

Dimensions: 223 x 13 h 162 cm

Poids: 23 Kg

Emballage trois boîtes: 92 x 21 x 77 cm 155 x 22 x 24 cm 51 x 51 x 28 cm

Volume emballage: 0,302 m³ Note: kit de suspension inclus. Frame


Year of production: 2015 Versions: matt, lacquered. Material: Polyethylene.

Dimensions: 223 x 13 h 162 cm

Weight: 23 Kg Packaging three boxes:

92 x 21 x 77 cm 155 x 22 x 24 cm 51 x 51 x 28 cm

Packaging volume: 0,302 m³ Note: hanging kit inluded.



SYMBOLS



For indoor use.



Stackable item.



Conformity to the European Community



100% recyclable polyethylene.



Recycling and disposal of electronic waste (WEEE).



Outdoor version on request (IP55).



European Community registered model.

LIGHTING SYMBOLS

 $For indoor \ and \ outdoor \ use.$



Protected against the intrusion of solid objects $\emptyset > 12$ mm, not against water.



Standard lamp base for E27 - 27 mm light bulb.



RGB lighting system.



Protected against the intrusion of solid objects $\emptyset > 1$ mm and splashing water.



Lamp base for G4 halogen bulb.



Item compatible with Candy Light.



Protected against the intrusion of dust and water jets.



Lamp base for GU10 spotlight.



Insulation class 1.



Fully protected against the intrusion of dust and immersion in water.



Lamp base for G13 neon tube.



Insulation class 2.



Small lamp base for E14 - 14 mm light bulb.



Neon tube lighting system.



Insulation class 3.



Medium lamp base for E26 - 26 mm light bulb.



LED technology lighting system.



Device proper to direct assembly onto normally inflammable surfaces.



Lighting through energy saving bulb.

The upper figure shows the number of allowed bulbs.

The lower figure shows the MAXIMUM recommended power.



Lighting through energy saving fluorescent spotlight.

The upper figure shows the number of allowed spotlights.

The lower figure shows the MAXIMUM recommended power.



Lighting through neon tube.

The upper figure shows the number of allowed neon tubes.
The lower figure shows the MAXIMUM recommended power.



Lighting through energy saving globe bulb.

The upper figure shows the number of allowed bulbs.

The lower figure shows the MAXIMUM recommended power.



Lighting through flexible LED tube.

The lower figure shows the MAXIMUM recommended power.



Lighting through circular T9 neon tube.

The upper figure shows the number of allowed neon tubes.

The lower figure shows the MAXIMUM recommended power.

WIRING SYMBOLS



Wiring with metal clamp. IP20 protection. Diameter 11 cm.



Wiring with special base for KIT LED 3 WATT. IP55 protection.

Diameter 11,6 cm.



Wiring with metal base.

IP55 protection.

Diameter 10 cm. Fastening by hex screw key.



Wiring with plastic screw base.

13 - IP20 protection. E3 - IP55 protection. Diameter 6 cm.



Wiring with metal base.

IP55 protection.

Diameter 20 cm. Fastening by hex screw key.



Wiring with plastic screw base.

13 - IP20 protection. E3 - IP55 protection. Diameter 10 cm.



Wiring with plastic base and metal inserts.

12 - IP20 protection. E2 - IP55 protection.

Diameter 10 cm. Fastening by slot screwdriver.



Wiring with plastic screw base.
13 - IP20 protection. E3 - IP55 protection.
Diameter 15 cm.



Wiring with plastic base and LED CANDY LIGHT.

IP44 protection.

Diameter 10 cm.



Special metal base. IP20 protection. Several sizes.

MATERIAL PROPERTIES

Material: Linear low-density polyethylene - LLDPE.

Production process: rotational moulding.

Resistant to extreme temperatures (-60°C to +80°C).

UV resistant (except for lighting colours).

High tensile strength.

WARNING

- Keep away from excessive heat sources.
- Avoid any improper use. Do not stand on the products. When the product has to be moved, lift the product off the ground in order to avoid damage.
- Do not overload the pot structure in order to avoid deforming.
- Carefully comply with the maintenance & cleaning instructions.
- In case of malfunctioning or damage of the wiring or any electrical parts, refer to a qualified electrician.

MAINTENANCE & CLEANING

- To prevent dust and dirt from sticking to the plastic surfaces, periodically clean the products with a damp cloth and neutral liquid soap diluted in water.
- Avoid using ethanol or any liquids containing, even in small amounts, acetone, trichloroethylene or ammonia (solvents in general).
- It is recommended the use of SLIDE's "CleanUp" cleaner or a degreaser. Spray the cleaning product on the surface, rub with a damp cloth and rinse abundantly with water (preferably with a high pressure washer). In case of persistent stains use a high pressure washer or scrub eraser.
 - The use of the scrub eraser (melamine foam Scotch-Brite® Easy Eraser or similar) is only recommended for white colour, as they are slightly abrasive.
- The lacquered version is also suitable for outdoor use, however it is more sensitive to scratches: periodically clean with a polish cleaner, gently rubbing with soft cloth/cotton wool.
- Cushions can be cleaned with a damp cloth, neutral liquid soap and water.
- For metal parts use specific cleaners.

SUSTAINABILITY & RECYCLING

All SLIDE products are 100% recyclable. Furthermore, grey, black and chocolate matt colours are produced with recycled polyethylene. SLIDE has a closed production cycle with no health prejudicial emissions and complying with ecological sustainibility rules.

When a product reaches the end of its life, do not treat the product or any of its parts as domestic waste. Dispose by sending to differentiated collection centres.

RESPONSIBILITY & RETURNS

SLIDE declines any liability to damages caused to things or persons by an illegitimate use of the product. SLIDE won't accept any returned goods without having checked the kind of defects first.

WARRANTY

SLIDE products are guaranteed against all manufacturing faults, granted that the items are appropriately used, for twenty-four (24) months from the date of purchase upon presentation of the invoice.

LED KITS only are guaranteed for twelve (12) months from the date of purchase.

Warranty doesn't include parts that are subject to wear and tear due to usage, batteries when provided, wiring and electrical parts that do not have manufacturing faults.

